

SPECIFICATION



TRIOPRO PRIMER 1200

Deep penetration primer

DESCRIPTION OF MATERIAL: One-component material being a water dispersion of styrene-acrylic copolymer with addition of various auxiliary substances.

DESIGNATION OF MATERIAL: Material is intended for priming of walls and ceilings inside and outside of premises before painting. Product is efficient on concrete, brick, plastered and putty-filled bases, as well as on gypsum-cardboards. It decreases absorbing ability of base, improves adhesion and longevity of coating. Product has nearly zero smell.

PHYSICAL PROPERTIES:

Color: Colorless.

Expenditure: 1 l per 9-11 m² for application in one layer, depending on the method of application and properties of the surface being painted.

Drying time:

Product name	Drying time at the temperature of 20°C with relative air humidity of 65%
To overlaying, not less than	8 h

SURFACE PREPARATION: Surface to be primed is to be dry and clean. Chalking, cracked and peeling old coatings are to be removed.

APPLICATION METHOD: Roller, brush.

STORAGE CONDITIONS: Storage period is 24 months from manufacturing date. It is recommended to store product in closed manufacturer's packing at temperatures from 5°C to 35°C. Paint with the additional labeling of 'Freeze-resistant' withstands up to 5 cycles of freezing to -20°C without loss of quality.

PACKING: Plastic buckets with capacity of 1, 3, 5 or 11 l.

HEALTH PROTECTION AND LABOR SAFETY: See Material Safety Data Sheet.