

# SPECIFICATION



## TRIOPRO FINISH 6000

Multi-purpose enamel

**DESCRIPTION OF MATERIAL:** One-component material being a suspension of pigments and fillers in water dispersion of styrene-acrylic copolymer with addition of various auxiliary substances.

**DESIGNATION OF MATERIAL:** Enamel is intended for painting of preliminarily primed or painted radiators and heating devices operated at temperatures up to 70°C, objects made of metal, wood (with the exception of floors), and cement-containing base layers.

**PHYSICAL PROPERTIES:**

**Color:** White (semi-matte or semi-glossy) color.  
Possibility to choose colors via computer color-selection systems or manually, with multi-purpose colorants or pigment paste for water-dispersion paint (in this case, it is recommended to check colorants for compatibility with paint).

**Expenditure:** 1 l per 8-12 m<sup>2</sup> for application in one layer, depending on the method of application and properties of the surface being painted.

**Drying time:**

Product name	Drying time at the temperature of 20°C with relative air humidity of 65%
From dust	1 h
To application of next layer, not less than	12 h
To gaining of full strength	72 h

**SURFACE PREPARATION:** Surface to be painted is to be dry and clean. Chalking, cracked and peeling old coatings are to be removed. Surfaces not painted earlier are to be coated with anti-corrosion primer.

**APPLICATION METHOD:** Sprayer, roller, brush.

**APPLICATION CONDITIONS:**

- Air temperature not lower than +5°C;
- Temperature of the surface being painted: not lower than +5°C;
- Do not apply during operation of central heating systems, on hot coils and radiators.

**STORAGE CONDITIONS:** Storage period is 24 months from manufacturing date.  
It is recommended to store product in closed manufacturer's packing at temperatures from 5°C to 35°C.  
Paint with the additional labeling of 'Freeze-resistant' withstands up to 5 cycles of freezing to -20°C without loss of quality.

**PACKING:** Plastic buckets with capacity of 1, 3, 5 or 11 l.

**HEALTH PROTECTION AND LABOR SAFETY:** See Material Safety Data Sheet.