

SPECIFICATION



TRIOPRO PRIMER 1000

Covering primer

DESCRIPTION OF MATERIAL: One-component material being a suspension of pigments and fillers in water dispersion of styrene-acrylic copolymer with addition of various auxiliary substances.

DESIGNATION OF MATERIAL: Material is intended for priming of facades, semi-basements of buildings, walls and ceilings in residential premises before painting. Product has good covering characteristics, decreases expenditure of paint on contrasting surfaces. It is applied on plaster, putty, bricks, surfaces painted earlier with water-dispersion paint, wallpaper, gypsum-cardboard sheets, chipboards, fiberboards, concrete.

PHYSICAL PROPERTIES:

Color: White (matte) color.

Expenditure: 1 l per 8-12 m² for application in one layer, depending on the method of application and properties of the surface being painted.

Drying time:

Product name	Drying time at the temperature of 20°C with relative air humidity of 65%
From dust	1 h
To overlaying, not less than	12 h

SURFACE PREPARATION:

Surface to be painted is to be dry and clean. Chalking, cracked and peeling old coatings are to be removed.

APPLICATION METHOD:

Sprayer, roller, brush.

APPLICATION CONDITIONS:

- Air temperature not lower than +5°C;
- Temperature of the surface being painted: not lower than +5°C.

STORAGE CONDITIONS:

Storage period is 24 months from manufacturing date.
It is recommended to store product in closed manufacturer's packing at temperatures from 5°C to 35°C.
Paint with the additional labeling of 'Freeze-resistant' withstands up to 5 cycles of freezing to -20°C without loss of quality.

PACKING:

Plastic buckets with capacity of 1, 3, 5 or 11 l.

HEALTH PROTECTION AND LABOR SAFETY: See Material Safety Data Sheet.