# Technical Data Sheet

## TRIOSOLV 0002

Thinner

| | |
|---|---|
| **MATERIAL DESCRIPTION:** | Mixed thinner based on volatile organic liquids: aromatic hydrocarbons, ketones, alcohols and esters |
| **DESTINATION:** | TRIOSOLV 0002 is designed for dilution of paints and coatings and washing of equipment used in the technological process of applying paints and varnishes |
| **PHYSICAL CHARACTERISTICS:** | |
| **Color and appearance:** | Colorless or slightly yellowish homogeneous transparent liquid without turbidity, delamination and suspended particles |
| **Density,** kg/l**:** | 0,870 ± 0,005 |
| **Open Cup Flash Point:** | plus 6°C |
| **Precautions:** | Handle with care. Before and during use, the Precautions set out on the packaging labels must be observed |
| **Application:** | The thinner should be applied to the recommended material and in the recommended amounts |
| **STORAGE:** | 12 months from the date of manufacture. It is recommended to store in a dry, dark place in an airtight factory package at a temperature not exceeding plus 30°C, avoid direct exposure to UV rays and other sources of heat. |
| **SHIPPING PACKAGING:** | It is supplied in euro buckets (capacity - 20 liters). |
| **HEALTH AND SAFETY:** | Read the Material Safety Data Sheet |